



A CSW Industrials Company

metacaulk®

WRAP STRIP

**A flexible strip of
highly intumescent
firestop material**

In case of fire, penetration is
sealed preventing the passage
of flames & hot gases

**NEW
LONGER
LENGTHS!**



Wrap strip systems for up to 14" PVC pipe



Wrap Strip

Intumescent Firestop Strip

Code	Description	Qty
66440	1" x 18' Roll	2
66441	1" x 36' Roll	4
66442	2" x 18' Roll	1
66443	2" x 36' Roll	2



FEATURES

- No cure time
- Easy to apply
- VOC compliant - CDPH Standard Method v1.2
- Long length means less waste
- Systems up to 14" PVC
- Highly intumescent
- Tested in accordance with ASTM E814 (UL 1479)
- Complies to UL required Accelerated Aging and High Humidity Testing

Application Simply wrap required number of strips around penetrating item to fill the annular space or as required by system design. When exposed to heat, expands to form a hard char to seal off the penetration.

Recommended for Plastic and insulated pipe applications



FBC™ SYSTEM COMPATIBLE INDICATES THAT THIS PRODUCT HAS BEEN TESTED, AND IS MONITORED ON AN ONGOING BASIS, TO ASSURE ITS CHEMICAL COMPATIBILITY WITH FLOWGUARD GOLD®, BLAZEMASTER® AND CORZAN® PIPING SYSTEMS AND PRODUCTS MADE WITH TEMPRITE® TECHNOLOGY. The FBC System Compatible Logo, FBC®, FlowGuard Gold®, BlazeMaster®, Corzan® and Temprite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.

RectorSeal, LLC 2601 Spenwick Drive - Houston, TX 77055 800-231-3345 rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50103-0121